



BC0609 Pallet Dolly



Suitable for loading and unloading P1,P6,P7,P9 pallets and LD1, LD2,LD3,LD4,LD6,LD7 containers.

Dimensions

Loading design	three-side	Wheel base	2180mm
Overall length	4900mm	Wheel gauge -front	1700mm
Overall width	2590mm	Wheel gauge -rear	1700mm
Overall height	630mm	Tire Type -front	400-8
Tow bar	1110mm	Tire Type -rear	400-8
Working surface size	3400*2590mm	Quantity of tires	8
Working surface	508mm	Max speed	32km/h
Weight	about 1098kg	Min turning radius	≤6500mm
Loading capacity	7000kg	Roller external diameter	φ60mm

Specification		Options
Steering	Castor front wheel	-
Loading	three side loading	-
Anti-collision	Anti-collision function is designed under the tow bar	-
Brake	Activated when the tow bar is lifted and lowered	-
Rollers	69 inverted casters and 9 guide rollers, all of which are galvanized	-
Stoppers	4 different types: (A) L-shaped restraint lock*8; (B) I-shaped restraint lock*6; (C) Centre stopper*2; (D) L-shaped Movable hook restraint lock*4	-
Hitch	Patented SUPU Hitch	Automatic Hitch
Finish	Sandblasted and painted	Hot-galvanized