



PD2008 Pallet Dolly



Suitable for loading and unloading P1,P6,P7,P9 pallets and LD1, LD2,LD3,LD4,LD6,LD7 containers.

Dimensions

Loading design	narrow side	Wheel base	1760mm
Overall length	4470mm	Wheel gauge -front	2500mm
Overall width	3550mm	Wheel gauge -rear	2500mm
Overall height	590mm	Tire Type-front	400-8
Tow bar	1510mm	Tire Type-rear	400-8
Working surface size	3550*2650mm	Quantity of tires	8
Working surface	520mm	Max speed	32km/h
Weight	about 1320kg	Min turning radius	≤6500mm
Loading capacity	7000kg	Roller external diameter	φ76mm

Specification

Options

Steering	Castor front wheel	Turntable type
Loading	Narrow side loading	-
Anti-collision	Anti-collision function is designed under the tow bar	-
Rollers	All galvanized, designed by 3 rows and 46 rollers	-
Stoppers	L-shaped stopper*4+ T-shaped stopper*1+168 stopper*6+155 stopper*6	Fingers with automatic locks
Brake	Activated when the tow bar is lifted and lowered	-
Hitch	Patented SUPU spring loaded hitch	Automatic Hitch
Finish	Sandblasted and painted	Hot-galvanized